

E-PoS E-Touch Integrated



Compact, Quality, But Affordable

New stylish and sleek designed E-Touch Integrated System, Now Powered with a P4 or a Mobile Celeron Processor.

The Compact E-Touch Integrated System is ideal for operating in limited space at affordable price. A choice of 15" Touch Screen with tilt angle from 0 ~ 70 Degree offers you maximum flexibility and convenience.

All I/O connectors are covered under the front/back bezel to provide easier maintenance and better cable management.

General Features:

- 15" TFT-LCD with Touch Panel
- Support Intel® Celeron® M 1.2GHz
- 4 USB 2.0 ports, 4 COM ports, 1 RJ11 for cash drawer
- Optional Customer Display (VFD/LCD/LED) or Second Display (8.4"/10.4"/12.1")
- Optional Magnetic Card Reader or Smart IC Card Reader



1. Tilt Angle 0 ~ 70 degree



2. 3 in 1 module supports MSR/ Smart IC Card/I-Button



3. Thumb Screw Design Easy to open rear cover



4. Easy to Maintain and Service Less than 4 screws to reach key components



5. Customer Display Pole type
VFD type (21~20)
LCD type (Graphic)



6. Front I/O cover

Mainboard	Integrated 12	Integrated 15	Integrated 17
Motherboard	B81		
CPU Supports	Intel FSB 400MHz SK478 CPU (P4 / Celeron / Mobile Celeron 1.2G)		

Core Logic	Intel 852GM & ICH4 FSB 400 MHz		
System Memory	2 x DIMM up to 1GB DDR		
Graphic Memory	Shared memory 8MB-64MB		
Mini PCI Socket	1		
Storage Devices			
HDD	1 x 3.5" Driver bay		
Flash Memory	Compact Flash (Type I& II)		
LCD / Touch Panel			
LCD Size	12.1" TFT	15" TFT	17" TFT
Brightness (nits)	up to 180 cd / m ²	up to 250 cd / m ²	up to 260 cd / m ²
Maximal Resolution	800 x 600 / 1024 x 768	1024 x 768	1280 x 1024
Touch Screen Type	Resistive		
Tilt Angle (Degree)	0 ~ 70		
External I / O Ports			
Front I / O			
USB	2 (V2.0)		
Power on/off	1 button		
Rear I / O			
PS / 2	1x Keyboard, 1 x Mouse		
USB	2 (V 2.0)		
Serial/COM	4 (Pin 1 / 9 with 5V / 12V)		
Parallel	1 port		
LAN (10 / 100)	1x RJ45		
2nd VGA Output	1 x male type connector with power		
Cash Drawer Port	2 (12V / 24V)		
Power Supply / Adapter	Internal 180W ATX power supply		
Environment			
EMC & Safety	FCC / CE Class A, LVD		
Operating Temperature	5 °C~ +35 °C		
Storage Temperature	-10 °C~ +60 °C		
Options			
Smart / IC Card Reader	RS-232 interface Half-Insert Type		
Magnetic Card Reader	3 Tracks (RS-232 / PS2 interface)		
Customer Display	VFD / LCD Pole Display		
I-Button	Dallas Key PS2 interface		
Wireless LAN	Mini PCI 802.11 a / b / g WI-FI card and antenna		
Dimension (W x D x H) mm	323 x 355 x 182-288	378 x 365 x 182-305	404 x 366 x 182-334

* The specification is subject to change without prior notice.

E-POS Systems (India) Pvt. Ltd.,
3078-3079, Oberoi Garden Estate,
Chandivili, Andheri East, MUMBAI 400072
Tel – 022-40360500 Fax – 022-40360514
E mail – sales@eposindia.co.in, helpdesk@eposindia.co.in