

## *E- Touch Smart*



POS 310(Black/White)



POS312(Black/White)

### 3. Specification

Item		Description
Main Board	B45	B46
CPU	GXM 233-266GP	VIA Eden ESP4K/5K/7K
Core Logic	NS GX1	VIA VT8606 + VT686B
LCD size	POS310	10" DSTN-LCD Anti-glare
	POS312	10.4" TFT LCD
Brightness	POS310	70~100cd/m <sup>2</sup>
	POS312	150 cd/m <sup>2</sup>
Display Function	(built-in) on NS-CS5530	
Compact Flash	(Secondary/IDE)Type 1, Socket supported	
HDD	(Primary/IDE)Internal Slim type 44pin header (optional)	
RAM	On-board 128MB, 1 x S.O.-DIMM up to 256MB	
Resolution	800 x 600	
Touch Screen	4 Wire Resistive type (Miontec )	
Touch Panel	Miontec 4 Wire (COM5)	
Serial Port	6, Pin 1/9 with +5V/+12V, COM4 for Card Reader, COM5 for Touch Screen, COM6 for Customer Display	
Cash Drawer	2(with 12V/24V Output, MAX 24V≤2A)	
LPT	1	
USB	2(V1.1)	
PS2	Keyboard x 1, Mouse x 1	
LAN	1, (10/100 Base-T), RTL-8100 Chipset	
Audio	Line Out, System Speaker support (LCD Function Board)	
Magnetic Card Reader	3 Tracks, Keyboard or RS232 type (COM4) (Optional)	
Customer Display	LED type, (COM6) (Optional)	
Programmable Keypad	32 keys with key lock, Smart IC Card Reader (Optional)	
Dallars Key	i-Button Key Reader (Keyboard type, Optional)	
Expansion Slot	Mini PCI Socket	
OS support	Windows 98/CE 4.1, Linux	Windows CE/ 98/ 2000/ XP, Linux
Power Supply	AC Adapter: Input 100 ~ 240V, Output 19V/90W Safety: UL, CUL, TUV, CB, CSA	
Spill-proof	Touch Screen Panel	
Dimension	200mm(W) x 185mm(E) x 250mm(H) / 7.9"(W) x 7.3"(E) x 7.8"~9.8" (H)	
Temperature	5°C~ 35°C, operating	
EMI	FCC/CE Class B, VCCI	

**E-POS Systems (India) Pvt. Ltd.,  
3078-3079, Oberoi Garden Estate,  
Chandivili, Andheri East, MUMBAI 400072  
Tel – 022-40360500 Fax – 022-40360514**

**E mail – [sales@eposindia.co.in](mailto:sales@eposindia.co.in), [helpdesk@eposindia.co.in](mailto:helpdesk@eposindia.co.in)**